

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION						
NFPA Rating: Health-2; Flammability-2; Reactivity-0; Special--None Manufactured For: Aftermarket Auto Parts Alliance, Inc. Address: 14351 Blanco Road San Antonio, Texas 78216-7723			HMIS Rating: Health-2; Flammability-2; Reactivity-0; Personal Protection-B DOT Description: Consumer Commodity ORM-D Identity (trade name as used on label): <b style="text-align: center;">PARTS MASTER FUEL INJECTOR CLEANER (ENGINE MAINTENANCE KIT)			
Date Prepared: 10/17/07 Prepared By: LMA/IB Information Calls: (770) 422-2071 DOT EMERGENCY RESPONSE PHONE NUMBER: (800) 424-9300		MSDS Number: BJ0075 Revision: 2 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA				
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
PETROLEUM DISTILLATE		8008-20-6 / 8052-41-3	No	100	100	d
ISOPROPYL ALCOHOL		67-63-0	No	400	200	d
NAPHTHALENE		91-20-3	Yes	10	10	d
WARNING: This product contains a chemical or chemicals known to the State of California to cause cancer.						
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Range: 130-580°F			Specific Gravity (H ₂ O = 1): 0.78			
Vapor Pressure (Aerosols) (PSIG@70°F): N/Ap			Vapor Pressure (Non-Aerosols) (mm Hg and Temperature): N/E			
Vapor Density (Air = 1): Greater than 1.			Evaporation Rate (butyl Acetate = 1): N/E			
Solubility in Water: Negligible			Water Reactive: No			
Appearance and Odor: Blue liquid; strong solvent odor.			VOC (Federal EPA Definition) = 97% (by weight)			
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
Flammability as per USA Flame Projection Test (aerosols): N/Ap		Auto Ignition Temperature: N/E		Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E		
FLASH POINT AND METHOD USED (non-aerosols): approx. 105° F. (TCC)			EXTINGUISHER MEDIA: Foam, dry chemical; use water spray to cool exposed surfaces.			
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.						
Unusual Fire & Explosion Hazards: Vapors may spread to distant ignition sources (pilot lights, welding equipment, electrical equipment, etc.) & flash back.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE			HAZARDOUS POLYMERIZATION <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR			
Incompatibility (materials to avoid): Acids and strong oxidizers.			Conditions to Avoid: Open flame, welding arcs, heat, sparks.			
Hazardous Decomposition Products: Includes, but not limited to smoke, fumes, carbon monoxide, carbon dioxide, various hydrocarbons.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: <input checked="" type="checkbox"/> INHALATION <input type="checkbox"/> INGESTION <input checked="" type="checkbox"/> SKIN ABSORPTION <input checked="" type="checkbox"/> EYE <input type="checkbox"/> NOT HAZARDOUS						
ACUTE EFFECTS:						
Inhalation: May cause headache, dizziness, asphyxia, anesthetic effects (CNS depression), and possible unconsciousness.						
Eye Contact: May cause mild irritation		Skin Contact: Irritation and/or dermatitis due to defatting of the skin. If high pressure skin injection occurs, within hours the tissues will become swollen, discolored, and extremely painful.				
Ingestion: Nausea, vomiting and diarrhea; possible chemical pneumonitis if aspirated into lungs.						
CHRONIC EFFECTS: Chronic overexposure has been suggested as a cause of mild, reversible liver effects in laboratory animals.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, CNS, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for at least 15 minutes; if irritated, seek medical attention.						
Skin Contact: Remove contaminated clothing; launder before re-use. Wash skin with soap and water; if irritated, seek medical attention.						
Inhalation: Remove to fresh air; resuscitate if necessary. If breathing is difficult, administer oxygen. Seek medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Seek immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by MSHA/NIOSH for organic vapor.						
Protective Gloves: Neoprene or nitrile gloves are suggested.			Eye Protection: Safety glasses recommended.			
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: Eyewash station.						
Hygienic Work Practices: Do not eat, drink or smoke in work areas. Wash hands after handling.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb spilled liquid with suitable medium. Do NOT flush to sewers or drains. Dispose according to local, state and federal regulations.						
Waste Disposal Methods: Ensure containers are empty prior to disposal. Dispose fluid according to local, state and federal regulations.						
Precautions To Be Taken In Handling & Storage: Store in original shipping containers in cool, dry area away from heat. Keep container closed when not in use.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Read and follow all label directions. Remove ignition sources. Avoid breathing vapors. Avoid food contamination.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only