

# MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

## IDENTITY AND MANUFACTURER'S INFORMATION

<b>NFPA Rating:</b> Health-1; Flammability-3; Reactivity-0; Special- -		<b>HMIS Rating:</b> Health-2; Flammability-3; Reactivity-0; Personal Protection-B	
<b>Manufactured For:</b> Aftermarket Auto Parts Alliance, Inc. <b>Address:</b> 2706 Treble Creek Road, Suite 100 San Antonio, Texas 78258-4496		<b>DOT Description:</b> Consumer Commodity ORM-D <b>Identity</b> (trade name as used on label): <b>PARTS MASTER WHITE LITHIUM GREASE                  PM#0725</b>	
Date Prepared: 2/20/06      Prepared By: RC/IB		MSDS Number: A00725      Revision- 15	
Information Calls: (770) 422-2071		NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA	
<b>DOT EMERGENCY RESPONSE PHONE NUMBER: (800) 424-9300</b>			

## SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
<b>ISOBUTANE / PROPANE BLEND</b>	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d
<b>ACETONE</b>	67-64-1	No	1000	750	d
<b>LITHIUM GREASE</b>	7620-77-1	No	N/E	N/E	d
<b>HEPTANE</b>	142-82-5	No	500	500	d
<b>HYDROTREATED LIGHT PETROLEUM DISTILLATE</b>	64742-47-8	No	5 mg/m3 (mist)	5 mg/m3 (mist)	d

## SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

<b>Boiling Point:</b> N/A	<b>Specific Gravity</b> (H2O=1): Concentrate Only = .77
<b>Vapor Pressure:</b> PSIG @ 70°F (Aerosols): 60-70 psig	<b>Vapor Pressure</b> (Non-Aerosols)(mm Hg and Temperature): N/A
<b>Vapor Density</b> (Air = 1): N/E	<b>Evaporation Rate</b> ( = 1): N/E
<b>Solubility in Water:</b> partially	<b>Water Reactive:</b> No
<b>Appearance and Odor:</b> White to off-white liquid streaming spray with solvent odor.	

## SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

<b>FLAMMABILITY</b> as per USA FLAME PROJECTION TEST (aerosols)	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E      % UEL: N/E
<b>EXTREMELY FLAMMABLE</b>		
<b>FLASH POINT AND METHOD USED</b> (non-aerosols): N/A	<b>SPECIAL FIRE FIGHTING PROCEDURES:</b> Use water fog to cool containers to prevent rupturing and bursting.	
<b>EXTINGUISHER MEDIA:</b> Foam, dry chemical, carbon dioxide.		
<b>Unusual Fire &amp; Explosion Hazards:</b> Do not expose aerosols to temperatures above 120°F or the container may rupture. Provide shielding to protect personnel.		

## SECTION 4 - REACTIVITY HAZARD DATA

<b>STABILITY</b> [ X ] STABLE [ ] UNSTABLE	<b>HAZARDOUS POLYMERIZATION</b> [ ] WILL [ X ] WILL NOT OCCUR
<b>Incompatibility</b> (Mat. to avoid): Oxygen & oxidants.	<b>Conditions to Avoid:</b> Open flame, welding arcs, heat, sparks.
<b>Hazardous Decomposition Products:</b> Carbon dioxide, carbon monoxide and trace thermal decomposition by products of PTFE.	

## SECTION 5 - HEALTH HAZARD DATA

<b>PRIMARY ROUTES OF ENTRY:</b> [ ] INHALATION [ ] INGESTION [ ] SKIN ABSORPTION [ X ] EYE [ ] NOT HAZARDOUS	
<b>ACUTE EFFECTS</b>	
<b>Inhalation:</b> Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible unconsciousness or asphyxiation.	
<b>Eye Contact:</b> Irritation	<b>Skin Contact:</b> Can cause skin defatting.
<b>Ingestion:</b> Possible chemical pneumonitis if aspirated into lungs.	
<b>CHRONIC EFFECTS:</b> (Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation of solvents may cause brain and other nervous system damage.	
<b>Medical Conditions Generally Aggravated by Exposure:</b> Asthma.	

## EMERGENCY FIRST AID PROCEDURES

<b>Eye Contact:</b> Flush with water for 15 minutes. If irritated, seek medical attention.
<b>Skin Contact:</b> Wash with soap and water. If irritated, seek medical attention.
<b>Inhalation:</b> Remove to fresh air. Resuscitate if necessary. Get medical attention.
<b>Ingestion:</b> <b>DO NOT INDUCE VOMITING.</b> Drink two large glasses of water. Get immediate medical attention.

## SECTION 6 - CONTROL AND PROTECTIVE MEASURES

<b>Respiratory Protection (specify type):</b> Not normally needed; however if vapor concentration exceeds TLV, use respirator approved for organic vapors by NIOSH in positive pressure mode.	
<b>Protective Gloves:</b> Solvent resistant.	<b>Eye Protection:</b> Safety glasses.
<b>Ventilation Requirements:</b> Normal room ventilation.	
<b>Other Protective Clothing &amp; Equipment:</b> None	
<b>Hygienic Work Practices:</b> Wash with soap and water after contact.	

## SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

<b>Steps To Be Taken If Material Is Spilled Or Released:</b> Cover with absorbent material and sweep up. Wash area to prevent slipping. Incinerate or landfill according to local, state or federal regulations.
<b>Waste Disposal Methods:</b> Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.
<b>Precautions To Be Taken In Handling &amp; Storage:</b> Do not puncture or incinerate containers. Do not store at temperatures above 120°F.
<b>Other Precautions &amp;/or Special Hazards:</b> KEEP OUT OF REACH OF CHILDREN.

*We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.*

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only