

# MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION						
<b>NFPA Rating:</b> Health-2; Flammability-3; Reactivity-0; Special-0 <b>Manufactured For:</b> Aftermarket Auto Parts Alliance, Inc. Address: 14351 Blanco Road Address: San Antonio, TX 78216-7723 Phone: (210) 492-4868			<b>HMIS Rating:</b> Health-2; Flammability-4; Reactivity-0; Personal Protection-B <b>DOT Hazard Classification:</b> ORM-D <b>Identity</b> (trade name as used on label): <b>PARTS MASTER CARB SPRAY/PART #1736</b>			
Emergency Response Number: 800-255-3924 <b>NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA</b>			Date Prepared: 09/14/95      Prepared By: DL/KD Information Calls: (770)422-2071			
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
TOLUENE		108-88-3	Yes	200	100	d
ALIPHATIC PETROLEUM DISTILLATE		8052-41-3	No	400	400	d
ISOPROPYL ALCOHOL		67-63-0	No	500	400	d
<b>WARNING: This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.</b>						
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
<b>Boiling Point:</b> N/A <b>Vapor Pressure:</b> PSIG @ 70°F (Aerosols): 85-100 <b>Vapor Density</b> (Air = 1): N/E <b>Solubility in Water:</b> Partial <b>Appearance and Odor:</b> Clear liquid, with aromatic solvent odor.			<b>Specific Gravity</b> (H <sub>2</sub> O=1): Concentrate Only = 0.85 <b>Vapor Pressure</b> (Non-Aerosols)(mm Hg and Temperature): N/A <b>Evaporation Rate</b> ( = 1): N/E <b>Water Reactive:</b> No			
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
<b>FLAMMABILITY</b> as per USA FLAME PROJECTION TEST (aerosols) <b>EXTREMELY FLAMMABLE</b>		Auto Ignition Temperature N/E		<b>Flammability Limits in Air by % in Volume:</b> % LEL: N/E      % UEL: N/E		
<b>FLASH POINT AND METHOD USED</b> (non-aerosols): N/A <b>SPECIAL FIRE FIGHTING PROCEDURES:</b> Self-contained breathing apparatus.			<b>EXTINGUISHER MEDIA:</b> Foam, dry chemical, carbon dioxide, water.			
<b>Unusual Fire &amp; Explosion Hazards:</b> Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
<b>STABILITY</b> [ X ] STABLE [ ] UNSTABLE <b>Incompatibility</b> (Mat. to avoid): Acids and strong oxidizers.			<b>HAZARDOUS POLYMERIZATION</b> [ ] WILL [ X ] WILL NOT OCCUR <b>Conditions to Avoid:</b> Open flame, welding arcs, heat, sparks.			
<b>Hazardous Decomposition Products:</b> CO, CO <sub>2</sub> .						
SECTION 5 - HEALTH HAZARD DATA						
<b>PRIMARY ROUTES OF ENTRY:</b> [ X ] INHALATION [ ] INGESTION [ X ] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS						
<b>ACUTE EFFECTS:</b> <b>Inhalation:</b> Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness. <b>Eye Contact:</b> Irritation <b>Skin Contact:</b> Irritation <b>Ingestion:</b> Possible chemical pneumonitis if aspirated into lungs. Nausea.						
<b>CHRONIC EFFECTS:</b> (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, kidney and/or lung damage. Lab animals have experienced anemia, liver, kidney, lung, blood damage to Glycol Ether EB. <b>Medical Conditions Generally Aggravated by Exposure:</b> May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
<b>Eye Contact:</b> Flush with water for 15 minutes. If irritated, seek medical attention. <b>Skin Contact:</b> Wash with soap and water. If irritated, seek medical attention. <b>Inhalation:</b> Remove to fresh air. Resuscitate if necessary. Get medical attention. <b>Ingestion:</b> <b>DO NOT INDUCE VOMITING.</b> Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
<b>Respiratory Protection (specify type):</b> If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor. <b>Protective Gloves:</b> Rubber gloves. <b>Eye Protection:</b> Safety glasses recommended. <b>Ventilation Requirements:</b> Adequate ventilation to keep vapor concentration below TLV. <b>Other Protective Clothing &amp; Equipment:</b> None <b>Hygienic Work Practices:</b> Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
<b>Steps To Be Taken If Material Is Spilled Or Released:</b> Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. Prevent from entering drains or sewers. <b>Waste Disposal Methods:</b> Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. <b>Precautions To Be Taken In Handling &amp; Storage:</b> Do not puncture or incinerate containers. Do not store at temperatures above 130°F. <b>Other Precautions &amp;/or Special Hazards:</b> <b>KEEP OUT OF REACH OF CHILDREN.</b> Avoid food contamination. Avoid breathing vapors. Remove ignition sources.						

*We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.*

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only