

DATE: 05/08/96

## 5875 Medium Acrylic Enamel Reducer

## MATERIAL SAFETY DATA SHEET

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 ( HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this MSDS before handling and disposing of this product.

Pass this information on to employees, customers, &amp; users of this product.

## SECTION 1. CHEMICAL PRODUCTS &amp; COMPANY IDENTIFICATION / HAZARD RATINGS

PRODUCT IDENTITY:	Blend # 9413 5875 Medium Acrylic Enamel Reducer	HEALTH RATINGS:	
COMPANY IDENTITY:	P.P.C., INC.	HEALTH (NFPA) =	2
COMPANY ADDRESS:	1000 ARMORY PLACE	HEALTH (HMIS) =	3
	BRANDENBURG, KY 40108	FLAMMABILITY =	3
COMPANY PHONE:	1-270-422-5561	REACTIVITY =	0
CHEMTREC PHONE:	1-800-424-9300		
REGULATORY INFO. NO.:	1-800-325-3751		

## SECTION 2. INGREDIENT &amp; REGULATORY INFORMATION

All components of this product are on the TSCA list.

## SARA Title III Section 313 Supplier Notification

This product contains the indicated <\*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372.

This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS#	WT. %	(REG.SECTION)	RQ (LBS)
*Toluene	108-88-3	37	(311, 312, 313, RCRA)	1000
Light Aliphatic Solvent Naphtha	*64742-89-8	Not Appl.	(311, 312)	None
Acetone	67-64-1	Not Appl.	(311, 312)	5000
*2-Butoxyethanol	111-76-2	8	(313)	None
*Mixed Xylenes	1330-20-7	< 5	(311, 312, 313, RCRA)	100
*Methanol	67-56-1	< 3	(311, 312, 313, RCRA)	5000
*Ethylbenzene	100-41-4	< 2	(311, 312, 313, RCRA)	1000

SARA SECTION 311/312 HAZARDS:	Acute Health, Chronic Health, Fire			
MATERIAL	CAS#	TWA (OSHA)	TLV (ACGIH)	HAP
Toluene	108-88-3	200 ppm	50 ppm	Yes
Light Aliphatic Solvent Naphtha	*64742-89-8	500 ppm	300 ppm	No
Acetone	67-64-1	1000 ppm	750 ppm	No
2-Butoxyethanol	111-76-2	50 ppm (s)	25 ppm (s)	Yes
Mixed Xylenes	1330-20-7	100 ppm	100 ppm	Yes
Methanol	67-56-1	200 ppm (s)	200 ppm (s)	Yes
Ethylbenzene	100-41-4	100 ppm	100 ppm	Yes

In addition to EPA Hazardous Air pollutants showing 'Yes' under "HAP" above, using manufacturers' data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%) =  
Benzene, Cumene

MATERIAL	CAS#	CEILING	STEL (OSHA/ACGIH)
Light Aliphatic Solvent Naphtha	*64742-89-8	None Known	0 ppm
Acetone	67-64-1	None Known	1000 ppm
Mixed Xylenes	1330-20-7	None Known	150 ppm
Methanol	67-56-1	None Known	250 ppm
Ethylbenzene	100-41-4	None Known	125 ppm

CALIFORNIA PROPOSITION 65: This product contains the following chemicals known to the state of California to cause cancer & reproductive toxicity:  
Benzene, Toluene

IF > 2356 POUNDS OF THIS PRODUCT IS IN ONE CONTAINER THE "RQ" IS EXCEEDED.

DOT SHIPPING NAME: Paint Related Material, 3, UN1263, PG II

DRUM LABEL: (FLAMMABLE LIQUID)

### SECTION 3. HAZARDS IDENTIFICATION

MATERIAL	CAS#	LOWEST KNOWN LETHAL DOSE DATA
Ethylene Glycol Butyl Ether	111-76-2	LOWEST KNOWN LD50 (ORAL) 320.0 mg/kg (Rabbits)
Ethylene Glycol Butyl Ether	111-76-2	LOWEST KNOWN LC50 (VAPORS) 700 ppm (Mice)
Ethylene Glycol Butyl Ether	111-76-2	LOWEST KNOWN LD50 (SKIN) 440.0 mg/kg (Rabbits)

THRESHOLD LIMIT VALUE: 80 ppm (Evaporated Blend)

CONTAINS: TOLUENE, LIGHT ALIPHATIC SOLVENT NAPHTHA, ACETONE, 2-BUTOXYETHANOL, MIXED XYLENES, METHANOL, ETHYLBENZENE

**DANGER!!**  
**EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE**  
**ACUTE HAZARDS**

#### EYE & SKIN CONTACT:

- Primary irritation to skin, defatting, dermatitis.
- Absorption through skin increases exposure.
- Primary irritation to eyes, redness, tearing, blurred vision.
- Liquid can cause eye irritation. Wash thoroughly after handling.

#### INHALATION:

- Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.
- Breathing vapor can cause irritation.
- Acute overexposure can cause damage to kidneys, blood, nerves, liver & lungs.

#### SWALLOWING:

- Harmful or fatal if swallowed.
- Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

**SUBCHRONIC HAZARDS / CONDITIONS AGGRAVATED****CONDITIONS AGGRAVATED**

Chronic overexposure can cause damage to kidneys, blood, nerves, liver, & lungs.

Persons with severe skin, liver or kidney problems should avoid use.

**CHRONIC HAZARDS****CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:**

This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA, or ACGIH, as of this date, greater or equal to 0.1%.

This product may contain less than 149 ppm of Benzene.

Not considered hazardous in such low concentrations.

Absorption thru skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus.

**SECTION 4. FIRST AID MEASURES PROCEDURES****EYE CONTACT:**

For eyes, flush with plenty of water for 15 minutes & get medical attention.

**SKIN CONTACT:**

In case of contact with skin immediately remove contaminated clothing.

Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

(Discard contaminated shoes)

**INHALATION:**

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped give artificial respiration. CALL A PHYSICIAN IMMEDIATELY!

**SWALLOWING:**

If swallowed, CALL A PHYSICIAN IMMEDIATELY! Do NOT induce vomiting.

Have patient lie down & keep warm. Vomiting may lead to pneumonitis, which may be fatal

**SECTION 5. FIRE FIGHTING MEASURES**

**AUTO IGNITION TEMPERATURE:** 287 C / 550 F (Lowest Component)

**LOWER FLAMMABLE LIMIT IN AIR (% by vol):** 1.6

**FLASH POINT (TEST METHOD):** -16 C / 2 F (TCC)

**FLAMMABILITY CLASSIFICATION:** Class I B

**EXTINGUISHING MEDIA**

NFPA Class B extinguishers (Carbon Dioxide or foam) for Class I B liquid fires.

**SPECIAL FIRE FIGHTING PROCEDURES**

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used.

Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots).

Use NIOSH approved positive-pressure self-contained breathing apparatus.

**UNUSUAL EXPLOSION AND FIRE PROCEDURES**

**EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE**

Keep container tightly closed.

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

Closed containers may explode if exposed to extreme heat.

Applying to hot surfaces requires special precautions.

Empty container very hazardous! Continue all label precautions

**SECTION 6. ACCIDENTAL RELEASE MEASURES****SPILL OR LEAK PROCEDURES**

Stop spill at source. Dike area & contain. Clean up remainder with absorbent materials. Mop up & dispose of. Persons without proper protection should be kept from area until cleaned up.

**WASTE DISPOSAL METHOD**

Recycle or dispose of observing local, state & Federal health, safety & pollution laws. If questions exist, contact the appropriate agencies.

**OTHER PRECAUTIONS**

Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone.

## SECTION 7. HANDLING AND STORAGE

## HANDLING

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

Use only with adequate ventilation. Avoid breathing of vapor or spray mist.

Do not get in eyes, on skin or clothing.

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier.

Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

## STORAGE

Vapors may ignite explosively & spread long distances. Prevent vapor buildup.

Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone.

Do not store above 49 C / 120 F. Store large amounts in structures made for OSHA Class I B liquids.

Keep container tightly closed & upright when not in use to prevent leakage.

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## EXPOSURE CONTROLS

Ventilate to keep vapors of this material below 40 ppm. If over TLV, in accordance with 29 CFR 1910.134, use NIOSH approved positive-pressure self-contained breathing apparatus. Consult Safety Equipment Supplier. Use explosion-proof equipment.

## VENTILATION

LOCAL EXHAUST	= Necessary
MECHANICAL (GENERAL)	= Acceptable
SPECIAL	= None
OTHER	= None

## PERSONAL PROTECTIONS:

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier.

Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

## SECTION 9. PHYSICAL DATA

APPEARANCE:	Liquid, Water-White
ODOR:	Ketone
BOILING RANGE:	56 91 172 C / 134 196 342 F
GRAVITY @ 60 F:	
API:	41.1
SPECIFIC GRAVITY (Water = 1):	.820
POUNDS / GALLON:	6.831
VOC'S (>0.44 LBS / SQ IN):	91.3 Vol. % / 748.7 g/L / 6.236 Lbs/Gal
TOTAL VOC'S (TVOC):	100.0 Vol. % / 820.0 g/L / 6.830 Lbs/Gal
NONEXEMPT VOC'S (CVOC):	85.5 Vol. % / 706.0 g/L / 5.880 Lbs/Gal
VAPOR PRESSURE (mm of Hg) @ 20 C	59.0
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)	19.6
VAPOR DENSITY (air = 1) :	3.0
WATER ABSORPTION:	Appreciable
SOLVENCY PARAMETERS:	
HKB (Hydrogen Bonding) :	21.2
PKB (Polarity) :	38.4
DKB (Dispersion) :	40.4
REFRACTIVE INDEX:	1.439

## SECTION 10. REACTIVITY DATA

## STABILITY

Stable

## CONDITIONS TO AVOID

Isolate from oxidizers, heat, sparks, electric equipment, & open flame.

**MATERIALS TO AVOID**

Isolate from strong oxidizers such as permanganates, chromates, & peroxides.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Carbon Monoxide, Carbon Dioxide from burning.

**HAZARDOUS POLYMERIZATION**

Will not occur.

**NOTICE**

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and / or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not related to its use in combination with any other material or process.