

***** SECTION 1: PRODUCT IDENTIFICATION *****

MANUFACTURERS ADDRESS : 1101 THIRD STREET SOUTH, MINNEAPOLIS, MN 55415
MFG TELEPHONE NUMBER : (612) 332-7371
24 HR EMERGENCY PHONE NO : 1-888-345-5732
CHEMICAL NAME OR FAMILY : PAINT PRODUCT
FORMULA : NOT APPLICABLE
TRADE NAME : 56 6499G AM EQ/IMP NEW CAT YL
REVISION DATE : 12-15-00 DATE PRINTED : 05-21-01

***** SECTION 2: HAZARDOUS INGREDIENTS *****

NAME	WT %		
COMMON(NA):MINERAL SPIRITS	35-40%	TLV TWA	100.00 PPM
		TLV STEL	NOT ESTAB
CAS:64742-47-8 CHEMICAL: DISTILLATES (PETROLEUM), HYDROTREATED LIGHT		OSHA PEL	500.00 PPM
		CEILING	NOT ESTAB
		RECOMND	NOT ESTAB
COMMON(1):CRYSTALLINE SILICA	.1-1.0%	TLV TWA	0.10 MG/CU M
		TLV STEL	NOT ESTAB
CAS:14808-60-7 CHEMICAL: QUARTZ		OSHA PEL	0.10 MG/CU M
		CEILING	NOT ESTAB
		RECOMND	NOT ESTAB
COMMON(NA):TITANIUM DIOXIDE	1-5%	TLV TWA	10.00 MG/CU M
		TLV STEL	NOT ESTAB
CAS:13463-67-7 CHEMICAL: TITANIUM OXIDE		OSHA PEL	10.00 MG/CU M
		CEILING	NOT ESTAB
		RECOMND	NOT ESTAB

THERE ARE NO SARA 313 CHEMICALS IN THIS PRODUCT

(1) = THIS MATERIAL IS A CARCINOGEN PER NTP, IARC

ALL COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH U.S. TSCA CHEMICAL SUBSTANCE INVENTORY REQUIREMENTS.

***** SECTION 3: PHYSICAL DATA *****

BOILING POINT: 315 DEG F. (157 DEG C.)
VAPOR PRESSURE MM HG AT 68 DEG F. (20 DEG C.): 2.0
VAPOR DENSITY (AIR = 1.0): 5.1
SPECIFIC GRAVITY: 1.08
PERCENT VOLATILE BY VOLUME: 53.18
EVAPORATION RATE (BUTYL ACETATE = 1): .1
SOLUBILITY IN WATER: NO
APPEARANCE/ODOR: NORMAL FOR A COATINGS PRODUCT.
PH : N.AV
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.AV

***** SECTION 4: FIRE AND EXPLOSION HAZARD *****

FLASH POINT TCC/PM DEG F : 104
FLASH POINT TCC/PM DEG C : 40
LOWER EXPLOSIVE LIMIT : 1.00
UPPER EXPLOSIVE LIMIT : 6.00
AUTO IGNITION - DEG F : N.AV DEG C : N.AV
SENSITIVITY TO IMPACT : NONE
SENSITIVITY TO STATIC DISCHARGE : N.AV

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM, AND/OR WATER FOG.

SPECIAL FIRE FIGHTING PROCEDURES:
FIRE FIGHTERS MUST WEAR SELF CONTAINED BREATHING APPARATUS OR AIR MASKS.
CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

***** SECTION 4: FIRE AND EXPLOSION HAZARD *****CONTINUED****
CONTAINS OXIDIZABLE MATERIALS. CONTAMINATED RAGS, WIPES, SAWDUST, ETC.
MAY CATCH FIRE SPONTANEOUSLY. STORE WASTE IN WATER-FILLED, CLOSED METAL
CONTAINERS UNTIL DISPOSED OF IN COMPLIANCE WITH ALL APPLICABLE REGULATIONS.

***** SECTION 5: HEALTH HAZARD DATA *****

THRESHOLD LIMIT VALUE: NOT REQUIRED FOR MIXTURE.

EFFECTS OF OVEREXPOSURE:

IMMEDIATE EFFECTS (ACUTE):

HARMFUL IF INHALED. MAY AFFECT THE BRAIN, NERVOUS SYSTEM OR RESPIRATORY SYSTEM, CAUSING DIZZINESS, HEADACHE, NAUSEA OR RESPIRATORY IRRITATION.

OVEREXPOSURE TO INGREDIENTS IN THIS PRODUCT MAY CAUSE NOSE AND THROAT IRRITATION, EYE IRRITATION, SKIN IRRITATION.

DELAYED EFFECTS (CHRONIC):

CONTAINS CRYSTALLINE SILICA. THE IARC HAS DETERMINED THAT CRYSTALLINE SILICA INHALED IN THE FORM OF QUARTZ OR CRISTOBALITE FROM OCCUPATIONAL SOURCES IS CARCINOGENIC TO HUMANS (GROUP 1). REFER TO IARC MONOGRAPH 68 IN CONJUNCTION WITH THE USE OF THESE MATERIALS. THE NTP HAS ALSO DETERMINED THAT CRYSTALLINE SILICA IS A KNOWN HUMAN CARCINOGEN IN THE FORM OF FINE, BREATHABLE PARTICLES. RISK OF CANCER DEPENDS ON DURATION AND LEVEL OF EXPOSURE. IN COATINGS PRODUCTS, RISK IS DUE PRIMARILY TO INHALATION OF SANDING DUST OR RESPIRABLE PARTICLES IN SPRAY MIST. PROLONGED EXPOSURE TO RESPIRABLE CRYSTALLINE QUARTZ (SILICA) MAY CAUSE DELAYED (CHRONIC) LUNG INJURY (SILICOSIS) NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE - ANY RESPIRATORY OR SKIN CONDITION.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION.
SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER.
INHALATION: IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO FRESH AIR.
SWALLOWING: IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY.

POSSIBLE ROUTES OF ENTRY: INHALATION, INGESTION, SKIN ABSORPTION.

***** SECTION 6: REACTIVITY DATA *****

THIS PRODUCT IS STABLE
CONDITIONS TO AVOID: NONE
INCOMPATIBILITY: NA

HAZARDOUS DECOMPOSITION PRODUCTS:
CARBON DIOXIDE/MONOXIDE METAL OXIDES

HAZARDOUS POLYMERIZATION: NONE

***** SECTION 7: SPILL OR LEAK PROCEDURES *****

VENTILATE AREA. AVOID BREATHING OF VAPORS. USE SELF-CONTAINED BREATHING APPARATUS OR AIRMASK FOR LARGE SPILLS IN A CONFINED AREA. WIPE UP OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP. AVOID ALL PERSONAL CONTACT.

WASTE DISPOSAL METHOD:

DISPOSE IN CHEMICAL DISPOSAL AREA OR IN A MANNER THAT COMPLIES WITH LOCAL, STATE, PROVINCIAL AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

***** SECTION 8: SPECIAL PROTECTION INFORMATION *****

RESPIRATORY PROTECTION:

UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ABOVE APPLICABLE LIMITS, NO RESPIRATOR IS REQUIRED. IF RESPIRATOR IS REQUIRED, THE APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) SHOULD BE WORN DURING APPLICATION. FOLLOW RESPIRATOR MANUFACTURERS DIRECTIONS FOR RESPIRATOR USE.

VENTILATION:

REQUIRED FOR SPRAYING OR IN A CONFINED AREA, VENTILATION EQUIPMENT SHOULD BE EXPLOSION PROOF.

PROTECTIVE GLOVES: USUAL HAND PROTECTION FOR PAINT APPLICATION.

EYE PROTECTION: FOR SPRAY APPLICATION, USE CHEMICAL GOGGLES AS A MINIMUM. OTHERWISE, USE SAFETY GLASSES WITH SIDE SHIELDS AS A MINIMUM.

OTHER PROTECTIVE EQUIPMENT: USUAL CLOTHING FOR PAINTING OPERATIONS.

***** SECTION 9: SPECIAL PRECAUTIONS *****

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT STORE ABOVE 120 DEG F. (49 DEG C.) BASED ON THE PRODUCT FLASH POINT AND VAPOR PRESSURE, SUITABLE STORAGE SHOULD BE PROVIDED IN ACCORDANCE WITH OSHA REGULATION 1910.106/ONTARIO OH&S REGULATION 851 SECTION 22. EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE, INCLUDING FLAMMABLE OR EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR CONTAINER. ALL LABEL WARNINGS MUST BE OBSERVED UNTIL THE CONTAINER HAS BEEN CLEANED OR RECONDITIONED.

ABBREVIATIONS USED:

OSHA-OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION;
IARC-INTERNATIONAL AGENCY FOR RESEARCH ON CANCER; LEL-LOWER EXPLOSIVE LIMITS;
UEL-UPPER EXPLOSIVE LIMITS; MG CU M-MILLIGRAMS PER METERS CUBED; MM-MILLIMETERS;
MPPCF-MILLIONS OF PARTICLES PER CUBIC FOOT; MSHA-MINE SAFETY AND HEALTH
ADMINISTRATION; NIOSH-NATIONAL INSTITUTE OF OCCUPATIONAL SAFETY AND HEALTH;
WHMIS-WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION SYSTEM; H-HOURS; HR-HOURS;
NA-NOT APPLICABLE; NOT EST-NOT ESTABLISHED; NTP-NATIONAL TOXICOLOGY PROGRAM;
PB-LEAD; PEL-PERMISSIBLE EXPOSURE LEVEL; PPM-PARTS PER MILLION;
TCC/PM-TAG CLOSED CUP/PENSKY-MARTEN; RECM-RECOMMENDED; TLV-THRESHOLD LIMIT VALUES.
N.AV-NOT AVAILABLE; N.AP-NOT APPLICABLE; C-CELSIUS; F-FAHRENHEIT

***** PREPARED BY SECTION *****

PREPARED BY: REGULATORY AFFAIRS DEPT.
MFG TELEPHONE NUMBER : (612) 332-7371
REVISION DATE : 12-15-00

DATE PRINTED : 05-21-01

***** DISCLAIMER SECTION *****

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. THE VALSPAR CORPORATION MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA. THE VALSPAR CORPORATION FURTHER ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS, OR THIRD PARTIES CAUSED BY THIS MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THIS MATERIAL.