

# AUTO VALUE

## MATERIAL SAFETY DATA SHEET

### SECTION I PRODUCT IDENTIFICATION AND USE

PRODUCT NAME/ IDENTIFICATION

7652 / 7653 ROCKER PANEL PROTECTOR (BEIGE / BLACK)

W.H.I.M.S. STATUS

**CONTROLLED**

W.H.I.M.S. CLASSIFICATION

Class B2 Flammable Liquid, Class D2B Toxic

PRODUCT IDENTIFICATION NUMBER

Mixture

PRODUCT USE

Protective Coating

MANUFACTURER

Pro Form Products Limited  
430 Harrop Drive  
Milton, Ont.  
L9T 3H2  
(905) 878-4990

SUPPLIER

Auto Value Associates, Inc.  
14351 Blanco Road  
San Antonio, TX  
78218-7723  
(210) 492-4868

### SECTION II HAZARDOUS INGREDIENTS

%	HAZARDOUS INGREDIENTS	UN/CAS#	LC50 (IVL)	LD50 (ORAL)	LD50 (DERMAL)
41.6	Heptane	142-82-5	(400 ppm)	N/D	N/D
10.5	Toluol	108-88-3	*8000 ppm/4hr (rate)	2500 mg/kg (rate)	14000 mg/kg

Actual LC 50 numbers are preceded by an asterisk \*. Where this information is not available a Threshold Limit value (ppm in brackets) may be provided as an indication of the inhalation severity of the ingredient.

### SECTION III PHYSICAL DATA

PHYSICAL STATE	COLOUR AND APPEARANCE			ODOUR THRESHOLD (ppm)
Jelled Liquid	Black (7652) Off-white (7653) with Mild Solvent Odour			N/D
VAPOUR PRESSURE (mm Hg)	VAPOUR DENSITY (Air=1)	EVAPORATION RATE	BOILING POINT (°C)	FREEZING POINT
45 @ 20 deg C	3.4	4.5	100	N/D
pH	SPECIFIC GRAVITY (kg/l)	COEFF WATER/OIL DIST.	SOLUBILITY IN WATER (20°C)	
N/D	1.013	N/D	Not Soluble	

### SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT  
 YES  NO  IF YES, UNDER WHICH CONDITIONS?  
 On contact with Ignition source, flame or temperature above flash point.

MEANS OF EXTINCTION  
 CARBON DIOXIDE  FOAM  FOG SPRAY  
 DRY CHEMICAL  WATER STREAM  OTHER (SEE SPECIAL PROC.)

SPECIAL PROCEDURES  
 Fire Fighters close enough to be in contact with fumes should wear self-contained breathing apparatus. Solvent vapours can flash-back and form explosive mixtures with air.

FLASHPOINT (°C) (METHOD)	LOWER FLAMMABLE LIMIT (% BY VOLUME)	UPPER FLAMMABLE LIMIT (% BY VOLUME)
-10 (TCC)	1.0	7.0
AUTOIGNITION TEMPERATURE (°C)	HAZARDOUS COMBUSTION PRODUCTS	
N/D	Oxides of Carbon	

EXPLOSIVE DATA	SENSITIVITY TO IMPACT	SENSITIVITY TO STATIC DISCHARGE
→	NONE	YES

### SECTION V REACTIVITY DATA

CHEMICAL STABILITY  
 YES  NO  IF NO, UNDER WHICH CONDITIONS?

INCOMPATIBLE SUBSTANCES  
 YES  NO  IF YES, WHICH ONES?  
 Strong Oxidizing Agents

REACTIVITY AND UNDER WHICH CONDITIONS?  
 None Known

HAZARDOUS DECOMPOSITION

Oxides of Carbon

PRODUCT IDENTIFIER

7658 ROCKER PANEL GUARD

**SECTION VI TOXICOLOGICAL PROPERTIES**

ROUTE OF ENTRY

 SKIN CONTACT   
  SKIN ABSORPTION   
  EYE CONTACT   
  INHALATION   
  INGESTION

EFFECTS OF ACUTE EXPOSURE TO PRODUCT

May cause dizziness or narcosis, and defatting of skin. Aspiration hazard. May irritate resp. tract. Effects are reversible. Overexposure to Toluene may cause nasal and brain damage.

EFFECTS IF CHRONIC EXPOSURE TO PRODUCT

Long term exposure may cause liver or kidney damage. Solvents listed have been reported to affect the Central Nervous System. May cause cardiac abnormalities.

LD-50 (ORAL)

2500 mg/kg (rats)

LD-50 (DERMAL)

N/D

LC - 50

8000 ppm 4hr/rats

EXPOSURE LIMITS:

100 ppm (TVL)

IRRITANCY OF PRODUCT:

Moderate

SENSITIZATION

Non-sensitizing

CARCINOGENICITY

Non-carcinogenic

TERATOGENICITY

Non-teratogenic

REPRODUCTIVE TOXICITY

None Known

MUTAGENICITY

None Known

SYNERGISTIC PRODUCTS

None Known

**SECTION VII PREVENTIVE MEASURES**

PERSONAL PROTECTIVE EQUIPMENT:

When spraying more than one-half can continuously or more than one can consecutively use NIOSH approved respirator. Wear goggles or face shield.

ENGINEERING CONTROLS:

Use with adequate ventilation. Electrical and mechanical equipment should be spark proof.

LEAK AND SPILL PROCEDURES:

Remove all ignition sources, turn off all electric motors, absorb with inert material. Keep spills away from municipal sewers.

WASTE DISPOSAL:

Dispose of as hazardous waste.

HANDLING PROCEDURES AND EQUIPMENT

Do not puncture container. Deep away from heat, sparks, and flames.

STORAGE REQUIREMENTS:

Store in Flammable goods area. (Not above 120 deg F.)

SPECIAL SHIPPING INFORMATION:

**FLAMMABLE AEROSOL****SECTION VIII FIRST AID MEASURES**

EYE CONTACT

Flush eyes with gentle stream of water for at least 15 minutes.

SKIN CONTACT

Rinse effected areas with mild soap and water. Remove contaminated clothing.

INHALATION

Remove victim to fresh air. Provide CPR and oxygen, if necessary.

ASPIRATION / INGESTION

DO NOT INDUCE VOMITING. If vomiting is spontaneous, keep head below waist to prevent entry into lungs.

OTHER

Do not administer adrenalin following overexposure. In all cases see a physician if any problems persist.

**SECTION IX PREPARATION DATE OF MSDS**

PREPARED BY

Marlene Speck

CANUTEC EMERGENCY PHONE NUMBER

(613)-896-8666

DATE

August 1, 1997

**WARRANTY AND DISCLAIMER.** The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Pro-Form Product's knowledge. The information relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Customer should read and understand this MSDS sheet, and package labeling before using the product. SELLER DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR ANY PARTICULAR PURPOSE. Seller will, at its option, either replace the goods sold or refund the purchase price. No warranty will apply if the goods are in any way altered or modified after delivery by the seller.