



Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product ID: 456.0100699.076
Product Name: AB699 GRAY SAND PRIMER 12U
Product Use: Paint product.
Print date: 05/Aug/2008
Revision Date: 26/Jul/2008

Company Identification

The Valspar Corporation - Architectural Coatings Division
1000 Lake Road
Medina, OH 44256

Manufacturer's Phone: 1-330-725-4511

24-Hour Medical Emergency Phone: 1-888-345-5732

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
Ingestion
Skin absorption

Eye Contact:

- Moderate eye irritation

Skin Contact:

- Dermatitis

Ingestion:

- Harmful if swallowed.

Inhalation:

- Causes respiratory tract irritation.
- Harmful by inhalation.
- May cause pulmonary edema.
- May cause bronchopneumonia or bronchitis.
- Exposure to high concentrations may cause pulmonary edema or excessive cadmium adsorption resulting in pulmonary emphysema, and/or liver and kidney dysfunction.

Target Organ and Other Health Effects:

- Causes headache, drowsiness or other effects to the central nervous system.
- Blood disorders
- May cause damage to mucous membranes.
- Liver injury may occur.
- Kidney injury may occur.

This product contains ingredients that may contribute to the following potential chronic health effects:

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Teratogens:

- May cause birth defects.

Carcinogens:

- Possible cancer hazard. Contains material which may cause cancer based on animal data.
- Cancer hazard. Contains material which can cause cancer.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| Ingredient Name CAS-No. | Approx. Weight % | Chemical Name |
|---|-----------------------------|------------------------------|
| DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1 | 35 - 40 | Acetone |
| PROPANE 74-98-6 | 15 - 20 | Propane |
| TALC 14807-96-6 | 5 - 10 | TALC (MG3H2(SI03)4) |
| BUTANE 106-97-8 | 5 - 10 | Butane |
| XYLENE 1330-20-7 | 5 - 10 | Xylenes (o-, m-, p- isomers) |
| TITANIUM DIOXIDE 13463-67-7 | 1 - 5 | Titanium dioxide |
| ISOPROPYL ALCOHOL 67-63-0 | 1 - 5 | Isopropyl alcohol |
| ETHYL 3- ETHOXYPROPIONATE 763-69-9 | 1 - 5 | Ethyl 3-ethoxypropionate |
| METHYL ETHYL KETONE 78-93-3 | 1 - 5 | Methyl ethyl ketone |
| ISOBUTYL ACETATE 110-19-0 | 1 - 5 | Isobutyl acetate |
| PROPRIETARY ADDITIVE | 1 - 5 | PROPRIETARY ADDITIVE |
| ETHYLBENZENE 100-41-4 | 1 - 5 | Ethyl benzene |

If this section is blank there are no hazardous components per OSHA guidelines.

4. FIRST AID MEASURES

Eye Contact:

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyes wide apart.

Skin Contact:

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

Ingestion:

Rinse mouth with water. Give one or two glasses of water. Never give anything by mouth to an unconscious person. Only induce vomiting at the instruction of medical personnel. Get medical attention.

Inhalation:

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration.

Medical conditions aggravated by exposure:

Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

| | |
|----------------------------------|---|
| Flash point (Fahrenheit): | -31°F (-35°C) |
| Lower explosive limit: | 1 % |
| Upper explosive limit: | 16 % |
| Autoignition temperature: | not determined -°F (°C) |
| Sensitivity to impact: | no |
| Sensitivity to static discharge: | Subject to static discharge hazards. Please see bonding and grounding information in Section 7. |
| Hazardous combustion products: | See Section 10. |

Unusual fire and explosion hazards:

Contaminated rags, wipes, saw dust, etc., may catch fire spontaneously. Store waste under water in closed metal containers or in approved self-closing containers designed to prevent spontaneous combustion until disposed of in compliance with applicable regulations. Oxidizing Material

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Keep containers and surroundings cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid contact with eyes.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Chemical goggles, also wear a face shield if splashing hazard exists.

Skin protection:

Appropriate chemical resistant gloves should be worn.

Other Personal Protection Data:

Ensure that eyewash stations and safety showers are close to the workstation location. To prevent skin contact wear protective clothing covering all exposed areas.

Respiratory protection:

Wear appropriate, properly fitted respirator (NIOSH approved) during spray application or in other situation where mists may be generated unless air monitoring vapor mist levels are below applicable limits-- where applicable limits have been established. When respirators are used, follow respirator manufacturers directions for use.

Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Use explosion-proof electrical/ventilating/lighting/equipment.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

| Ingredient Name CAS-No. | Approx. Weight % | TWA (final) | Ceilings limits (final) | Skin designations |
|---|---------------------|--|-------------------------|-------------------|
| DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1 | 35 - 40 | 2400 mg/m ³ 1000 ppm | | |
| PROPANE 74-98-6 | 15 - 20 | 1800 mg/m ³ 1000 ppm | | |
| TALC 14807-96-6 | 5 - 10 | Respirable. Listed. Total dust. Listed. | | |
| XYLENE 1330-20-7 | 5 - 10 | 435 mg/m ³ 100 ppm | | |
| TITANIUM DIOXIDE 13463-67-7 | 1 - 5 | 15 mg/m ³ Total dust. | | |
| ISOPROPYL ALCOHOL 67-63-0 | 1 - 5 | 980 mg/m ³ 400 ppm | | |
| METHYL ETHYL KETONE 78-93-3 | 1 - 5 | 590 mg/m ³ 200 ppm | | |
| ISOBUTYL ACETATE 110-19-0 | 1 - 5 | 700 mg/m ³ 150 ppm | | |
| ETHYLBENZENE 100-41-4 | 1 - 5 | 435 mg/m ³ 100 ppm | | |

ACGIH Threshold Limit Value (TLV's)

| Ingredient Name CAS-No. | Approx. Weight % | TWA | STEL | Ceiling limits | Skin designations |
|---|---------------------|----------|---------|----------------|-------------------|
| DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1 | 35 - 40 | 500 ppm | 750 ppm | | |
| PROPANE 74-98-6 | 15 - 20 | 1000 ppm | | | |

| Ingredient Name CAS-No. | Approx. Weight % | TWA | STEL | Ceiling limits | Skin designations |
|--------------------------------|---------------------|---|---------|----------------|----------------------|
| TALC 14807-96-6 | 5 - 10 | 2 mg/m ³ Respirable fraction. The value is for particulate matter containing no asbestos and <1% crystalline silica. | | | |
| BUTANE 106-97-8 | 5 - 10 | 1000 ppm | | | |
| XYLENE 1330-20-7 | 5 - 10 | 100 ppm | 150 ppm | | |
| TITANIUM DIOXIDE 13463-67-7 | 1 - 5 | 10 mg/m ³ | | | |
| ISOPROPYL ALCOHOL 67-63-0 | 1 - 5 | 200 ppm | 400 ppm | | |
| METHYL ETHYL KETONE 78-93-3 | 1 - 5 | 200 ppm | 300 ppm | | |
| ISOBUTYL ACETATE 110-19-0 | 1 - 5 | 150 ppm | | | |
| ETHYLBENZENE 100-41-4 | 1 - 5 | 100 ppm | 125 ppm | | |

9. PHYSICAL PROPERTIES

| | |
|---|-----------------------------------|
| Odor: | Normal for this product type. |
| Physical State: | Aerosol |
| Vapor pressure: | NOT DETERMINED mmHg @ 68°F (20°C) |
| Vapor density (air = 1.0): | 5.0 |
| Boiling point: | -44°F (-42°C) |
| Solubility in water: | not determined |
| Coefficient of water/oil distribution: | not determined |
| Density (lbs per US gallon): | 6.74 |
| Specific Gravity: | .81 |
| Evaporation rate (butyl acetate = 1.0): | 5.7 |
| Flash point (Fahrenheit): | -31°F (-35°C) |
| Lower explosive limit: | 1 % |
| Upper explosive limit: | 16 % |
| Autoignition temperature: | not determined -°F (°C) |

10. STABILITY AND REACTIVITY

| | |
|-----------------------------------|--|
| Stability: | Stable under normal conditions. |
| Conditions to Avoid: | Heat. |
| Incompatibility: | Strong oxidizing agents |
| Hazardous Polymerization: | None anticipated. |
| Hazardous Decomposition Products: | Silicon dioxide. Carbon monoxide and carbon dioxide. Metal oxide fumes. Nitrogen compounds. |

Sensitivity to static discharge: Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

11. TOXICOLOGICAL INFORMATION

| Ingredient Name CAS-No. | Approx. Weight % | NIOSH - Selected LD50s and LC50s |
|---|---------------------|--|
| DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1 | 35 - 40 | Inhalation LC50 Rat : 50100 mg/m ³ /8H Inhalation LC50 Mouse : 44 gm/m ³ /4H Oral LD50 Rat : 5800 mg/kg Oral LD50 Mouse : 3 gm/kg |
| BUTANE 106-97-8 | 5 - 10 | Inhalation LC50 Rat : 658 gm/m ³ /4H Inhalation LC50 Mouse : 680 gm/m ³ /2H |
| XYLENE 1330-20-7 | 5 - 10 | Inhalation LC50 Rat : 5000 ppm/4H Oral LD50 Rat : 4300 mg/kg Dermal LD50 Rabbit : >1700 mg/kg |
| ISOPROPYL ALCOHOL 67-63-0 | 1 - 5 | Inhalation LC50 Rat : 16000 ppm/8H Oral LD50 Rat : 5045 mg/kg Oral LD50 Mouse : 3600 mg/kg Dermal LD50 Rabbit : 12800 mg/kg |
| ETHYL 3- ETHOXYPROPIONATE 763-69-9 | 1 - 5 | Oral LD50 Rat : 5 gm/kg Dermal LD50 Rabbit : 10 mL/kg |
| METHYL ETHYL KETONE 78-93-3 | 1 - 5 | Inhalation LC50 Rat : 23500 mg/m ³ /8H Inhalation LC50 Mouse : 32 gm/m ³ /4H Oral LD50 Rat : 2737 mg/kg Oral LD50 Mouse : 4050 mg/kg Dermal LD50 Rabbit : 6480 mg/kg |
| ISOBUTYL ACETATE 110-19-0 | 1 - 5 | Oral LD50 Rat : 13400 mg/kg Dermal LD50 Rabbit : >17400 mg/kg |
| PROPRIETARY ADDITIVE | 1 - 5 | Oral LD50 Rat : >5 gm/kg Oral LD50 Mouse : >5 gm/kg |
| ETHYLBENZENE 100-41-4 | 1 - 5 | Oral LD50 Rat : 3500 mg/kg Dermal LD50 Rabbit : 17800 uL/kg |

Mutagens/Teratogens/Carcinogens:

May cause birth defects.

Possible cancer hazard. Contains material which may cause cancer based on animal data. Cancer hazard. Contains material which can cause cancer.

Contains ethylbenzene, which has been determined by NTP to be an animal carcinogen with no known relevance to humans. IARC has classified ethylbenzene as possibly carcinogenic to humans (2b) on the basis of sufficient evidence of carcinogenicity in laboratory animals but inadequate evidence of cancer in humans. Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA.

| Ingredient Name CAS-No. | Approx. Weight % | IARC Group 1 - Human Evidence | IARC Group 2A - Limited Human Data | IARC Group 2B - Sufficient Animal Data |
|--------------------------------|---------------------|----------------------------------|---------------------------------------|---|
| TITANIUM DIOXIDE 13463-67-7 | 1 - 5 | | | 2B Possible Carcinogen |
| ETHYLBENZENE 100-41-4 | 1 - 5 | | | Monograph 77, 2000 |

| Ingredient Name CAS-No. | Approx. Weight % | NTP Known Carcinogens | NTP Suspect Carcinogens | NTP Evidence of Carcinogenicity |
|----------------------------|---------------------|--------------------------|----------------------------|------------------------------------|
|----------------------------|---------------------|--------------------------|----------------------------|------------------------------------|

| | | | | |
|--------------------------|--------|--|--|--|
| TALC 14807-96-6 | 5 - 10 | | | male rat-some evidence; female rat-clear evidence; male mice-no evidence; female mice- no evidence |
| ETHYLBENZENE 100-41-4 | 1 - 5 | | | male rat-clear evidence; female rat-some evidence; male mice- some evidence; female mice-some evidence |

| Ingredient Name CAS-No. | Approx. Weight % | OSHA Select Carcinogens | OSHA Possible Select Carcinogens | ACGIH Carcinogens |
|----------------------------|---------------------|----------------------------|-------------------------------------|---|
| ETHYLBENZENE 100-41-4 | 1 - 5 | | | Group A3 Confirmed animal carcinogen with unknown relevance to humans. |

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations

Dispose of waste at an approved hazardous waste treatment/disposal facility in accordance with applicable local, provincial and federal regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

Proper Shipping Name: CONSUMER COMMODITY ORM-D
UN ID Number: CONCOM

U.S. Highway & Rail Shipments

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

Reportable Quantity Description:

International Air Transport Association (IATA):

Proper Shipping Name: AEROSOLS, FLAMMABLE
Hazard Class: 2.1
UN ID Number: UN1950

International Maritime Organization (IMO):

Proper Shipping Name: AEROSOLS
Hazard Class: 2
Non-Bulk UN ID Number: UN1950

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

| Ingredient Name CAS-No. | Approx. Weight % | SARA 302 | SARA 313 | CERCLA RQ in lbs. |
|----------------------------|---------------------|----------|----------|-------------------|
| | | | | |

| | | | | |
|---|---------|--|---|------|
| DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1 | 35 - 40 | | | 5000 |
| XYLENE 1330-20-7 | 5 - 10 | | form R reporting required for 1.0% de minimis concentration | 100 |
| METHYL ETHYL KETONE 78-93-3 | 1 - 5 | | form R reporting required for 1.0% de minimis concentration | 5000 |
| ISOBUTYL ACETATE 110-19-0 | 1 - 5 | | | 5000 |
| ETHYLBENZENE 100-41-4 | 1 - 5 | | form R reporting required for 1.0% de minimis concentration | 1000 |

SARA 311/312 Hazard Class:

Acute: yes
Chronic: yes
Flammability: yes
Reactivity: no
Sudden Pressure: yes

U.S. STATE REGULATIONS:

Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

Pennsylvania Right To Know:

| | |
|---------------------------------|--------------|
| TALC | 14807-96-6 |
| TITANIUM DIOXIDE | 13463-67-7 |
| ETHYL 3-ETHOXYPROPIONATE | 763-69-9 |
| ISOBUTYL ACETATE | 110-19-0 |
| ETHYLBENZENE | 100-41-4 |
| XYLENE | 1330-20-7 |
| ISOPROPYL ALCOHOL | 67-63-0 |
| PROPRIETARY ADDITIVE | Trade Secret |
| METHYL ETHYL KETONE | 78-93-3 |
| DIMETHYL KETONE- EXEMPT SOLVENT | 67-64-1 |
| PROPANE | 74-98-6 |
| BUTANE | 106-97-8 |

California Proposition 65:

WARNING! This product contains a chemical known in the State of California to cause cancer.

Rule 66 status of product

Photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories

US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

16. OTHER INFORMATION

16. OTHER INFORMATION

HMIS Codes

| | |
|----------------------|--|
| Health: | 3* |
| Flammability: | 4 |
| Reactivity: | 1 |
| PPE: | X - See Section 8 for Personal Protective Equipment (PPE). |

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Preparation Information:

| | |
|----------------|-------------------------------|
| Prepared By: | Regulatory Affairs Department |
| Print date: | 05/Aug/2008 |
| Revision Date: | 26/Jul/2008 |